

# SAMPLE DRAWING

FULL SIZE DRAWING WILL BE PROVIDED IN AUTOCAD FORMAT BY  
TREATMENT PLANT SERVICES AND SHALL BE USED BY DESIGN ENGINEER  
IN PREPARING PUMP STATION CONSTRUCTION DRAWINGS.


STANDARD DRAWING NO. 1070

## GENERAL TITLE SHEET



# PUMP STATION STANDARD DRAWINGS

## Location Map



## Drawing Index

SHEET #	DWG. #	SHEET TITLE	SHEET #	DWG. #	SHEET TITLE	SHEET #	DWG. #	SHEET TITLE
1	G00	GENERAL TITLE SHEET	15	1017	HEAVY DUTY CHAIN HOLDER	23	E00	ELECTRICAL SYMBOLS LEGEND
2	G01	GENERAL CWS DRAFTING PROCEDURES	16	1018	SINGLE PIPE TRENCH DETAIL	24	E01	ELECTRICAL ONE-LINE DIAGRAM
3	1001	DESIGN DATA TABLE 1 OF 2	17	1020	LANDSCAPE DETAILS	25	E02	ELECTRICAL INTERIOR ENCLOSURE - 01
4	1002	DESIGN DATA TABLE 2 OF 2	18	1021	LANDSCAPE DETAILS	26	E03	ELECTRICAL INTERIOR ENCLOSURE - 02
5	1003	CONCEPTUAL SITE SCHEMATIC	19	1022	LANDSCAPE DETAILS	27	E04	ELECTRICAL CONTROL PANEL DETAIL
6	1005	CHAIN LINK FENCE AND GATE	20	1023	LANDSCAPE DETAILS	28	E05	ELECTRICAL SEQUENCE CONTROL DIAGRAM
7	1007	FORCE MAIN PRESSURE GAUGE	21	1024	LANDSCAPE DETAILS	29	E06A	ELECTRICAL STARTER SCHEMATICS
8	1009	YARD HYDRANT	22	1025	LANDSCAPE DETAILS	30	E06B	ELECTRICAL STARTER SCHEMATICS
9	1011	REDUCED PRESSURE BACKFLOW				31	E07	ELECTRICAL ENCLOSURE AND RAIN HOOD, DETAIL REFERENCE
10	1012	BYPASS MANHOLE				32	E08	ELECTRICAL INTRINSICALLY SAFE EXAMPLE
11	1013	ARV RELEASE VALVE ASSEMBLY PLAN VIEW				33	E09	MECHANICAL DETAILS
12	1014	ARV RELEASE VALVE ASSEMBLY ELEVATION VIEW				34	E10	ELECTRICAL DISCONNECT AIR-GAP JUNCTION BOX DETAIL
13	1015	MUSHROOM STYLE ARV VENT & VALVE BOX DETAILS				35	E11	ELECTRICAL DETAILS
14	1016	TRACER BOX & PIPE WARNING SIGN DETAILS				36	E12	MISSION RTU, INTERCONNECTION DIAGRAM

JULY 2018

Plotted: 8/26/19 at 1:45pm By: egestorov  
File: W:\PS\CD\Drawings\Standards\STANDARDS\ELECTRICAL\2018\PS-STD\CAD\1070 DWG.CDR.dwg TAB:G00

DRN: ANV	ORIG DATE: 06/10/03
DSN:	DWG #: PS G00
CHK: JT	CAD FILE #: 1070PS00G00
APPD: JTO	SCALE: NA

THIS BAR IS ONE INCH  
WHEN DRAWING IS FULL  
SCALE.

2	02/17	CG	JT	STANDARD DRAWINGS UPDATE
1	2/07	CAD	DP	MINOR REVISIONS
REV #	DATE	DRN	APPD	DESCRIPTION

**CleanWater Services**  
Our commitment is clear.  
2550 SW Hillsboro Hwy. Hillsboro, Oregon 97123-9379

PROJ NAME: PUMP STATION  
STANDARD  
DRAWINGS

SHEET TITLE: GENERAL  
TITLE SHEET

SHEET: 1 OF: 36  
PLOT DATE: 8/26/19  
PLC #: NA  
CWS PROJ #: XXXX

DWG #: PS G00  
LAST UPDATE 07-25-2018  
ENGR STAMP:

# SAMPLE DRAWING

FULL SIZE DRAWING WILL BE PROVIDED IN AUTOCAD FORMAT BY  
TREATMENT PLANT SERVICES AND SHALL BE USED BY DESIGN ENGINEER  
IN PREPARING PUMP STATION CONSTRUCTION DRAWINGS.

## GENERAL CES DRAFTING PROCEDURES LAYERS, COLORS, & TEXT

STANDARD DRAWING NO. 1070B

### CWS STANDARD DRAFTING PROCEDURES

#### *Layers:*

1. Insert all xrefs on one layer named "XREF". The color of this layer should be grey.
2. Put all paperspace viewports on one layer named "DEFPPOINTS". Objects on this layer do not print, but are visible on screen. If for some reason you cannot use defpoints then use "PS-VPORTS".
3. Please put all paperspace objects on layers with a prefix "PS-XXXX" except the viewports if using defpoints. Ex: PS-TB for the titleblock.
4. All other layers should be set up according to the standard used by the client, as long as they are descriptive and somewhat close to the national standard. No numbered layers please. Preferably discipline prefixes on layer titles.
5. **BLOCKS:** When using blocks in our drawings please create them on layer '0' and set them to 'color by layer' before blocking them. Layer '0' should always be 'white'. This will allow blocks to take on the color of any layer they are added to. When creating projects or records from as-builts, it is often necessary to disassociate object colors to greyscale. It is very difficult to do this when there are multiple colors and layers attached to blocks.

#### *Colors:*

1. Please DO NOT draft using the color YELLOW or anything similar. Yellows DO NOT print well if the plot styles are unavailable. People other than CAD operators often want to view and manipulate CAD dwgs via voloview or other programs. When there are yellow objects throughout the drawings they are illegible to simply view. A CAD operator is then needed to fix plotstyles, pens, or layers. Yellow is so light against a white screen and paper that it can't be read in voloview and again doesn't print well. Please DO NOT draft using the color YELLOW or anything similar.

#### *Text:*

1. "Arial" is our CWS standard text with a full size text height of 0.125 inches for regular text, 0.250 for titles, and 0.1875 with a 10 deg. obliquing angle for identifiers and whatnot. Arial is the text style used in this document. All three sizes are represented here. Text on half size 11x17 drawings should be no smaller than 0.0625".
2. New text should ALWAYS be put on a layer set to color BLACK. Do not draft text in other colors and set pens to black. Draft text on a layer set to the black pen to ensure that important text info always prints and views clear. If there's a need to differentiate between new and existing text, place existing text on a grey, "?-TEXT-E" layer.

DRN: ANV	ORIG DATE: 06/10/03
DSN:	DWG #: PS G00
CHK: JT	CAD FILE #: 1070BPS00G00
APPD: JTO	SCALE: NA

THIS BAR IS ONE INCH  
WHEN DRAWING IS FULL  
SCALE.

2	02/17	CG	JT	STANDARD DRAWINGS UPDATE
1	2/07	CAD	DP	MINOR REVISIONS
REV #	DATE	DRN	APPD	DESCRIPTION



2550 SW Hillsboro Hwy. Hillsboro, Oregon 97123-9379

PROJ NAME: PUMP STATION  
STANDARD DRAWINGS

HEET TITLE: GENERAL  
CWS DRAFTING PROCEDURES  
LAYERS, COLORS, & TEXT

HEET: 2 OF: 36  
PLOT DATE: 8/26/19  
PLC #: NA  
CWS PROJ #: XXXX

DWG #: PS G01  
ENGR STAMP:

LAST UPDATE  
07-25-2018

## BASIN CHARACTERISTICS

Location:	Address and Cross Street
Basin Area:	XXX Acres
Equivalent Dwelling Units (EDU) Per Acre:	X.X
Persons Per EDU:	X.X
Population Equivalent	XXXX
Average Per Capita Flow:	XX GPD
Infiltration and Inflow, Peak Wet Weather Flow (PWWF)	XXX,XXX GPD
Average Daily Flow (ADF)	XXX,XXX GPD
Peak Hourly Flow:	XXX GPM

## PUMP STATION

Type:	Duplex submersible, non-clog, variable speed pumps
Capacity (per pump):	XXX GPM @ XX feet TDH (static head = XX ft)
Horsepower (HP):	XX HP Each with Variable Frequency Drives
Motor Data:	XXX volt xphase xx cycle
Firm Capacity of Pump Station:	X.XX MGD (XXX GPM)
Maximum Pump Starts Per Hour:	X
Wet Well Volume:	XXXX gallons (pumps off to lead pump on)
Level Control Type:	Pressure Transducer and backup floats
Overflow Point:	Manhole Number and Elevation
Overflow Location:	Description
Average Time To Overflow:	Time and Description xx hours at yy gpm Design Average Influent Flow
Telemetry:	Missions (owner-supply)
Transfer Switch:	Automatic
Standby Power Type:	XXX kW stationary diesel-powered standby generator
Fuel Tank Capacity:	xx Hrs (XXX Gallons)
EPA Reliability Class:	1
Flow Meter	X" Magnetic (Description)
Control	Constant Speed or VFD

## DATA TABLE SHEET 1 OF 2

### WASTEWATER PUMP STATION & FORCE MAIN DESIGN DATA TABLE

DRAWING NO. 1001

REVISED 07-18




<b>FORCE MAIN</b>	
Type and Length:	XXXX feet (Type?)
Forcemain Velocity:	X.X feet per second
Profile:	Description
Air Release Valve:	Quantity? Description?
Discharge Location:	Manhole Number and Elevation
Average Detention Time:	XX hours
Sulfide Control System:	Description?

<b>OPERATING LEVELS</b>	
Ground Elevation	XXX.XX
Overflow Alarm Elevation	Float Control System? (backup) XXX.XX
Lag Pump On/High Water Alarm Elevation	XXX.XX (provide distance from wet well floor in feet) same as level indicator digital display.
Lead Pump On Elevation	XXX.XX (provide distance from wet well floor in feet) same as level indicator digital display.
All Pumps Off Elevation	XXX.XX (provide distance from wet well floor in feet) same as level indicator digital display.
Wetwell Floor Elevation	XXX.XX (provide distance from wet well floor in feet) same as level indicator digital display.

<b>LANDSCAPING</b>	
Landscaping Area:	Square feet and Description
Irrigation System:	Type
Control Valves:	Number and Type
Backflow Device	Size and Type

## DATA TABLE SHEET 2 OF 2

<b>WASTEWATER PUMP STATION &amp; FORCE MAIN DESIGN DATA TABLE</b>	 <b>CleanWater Services</b>
DRAWING NO. 1002	REVISED 07-18



CONCEPTUAL SITE SCHEMATIC

DRAWING NO. 1003


REVISED 07-18

CleanWater Services

NOTES:

1. ALL FITTINGS, FASTENERS, & AND FABRIC TIES SHALL BE HOT DIP GALV.
2. CONC SHALL BE MIN 2500 PSI @ 28 DAYS.
3. PROVIDE BRACE RAIL BETWEEN END POSTS AND LINE POSTS. LENGTHS AS REQ'D.
4. PROVIDE GATE STOPS AND DROP RECEIVERS SET IN CONCRETE, EACH GATE.
5. PROVIDE EXTENSION ARMS ON LINE, END AND CORNER POSTS & GATE POSTS AS REQ'D.
6. CENTER BRACE RAIL NOT REQUIRED WITH FENCE HEIGHT OF 5' OR LESS.
7. ALL POSTS AND RAILS TO MATCH FENCE COLOR.

MEMBER	NOMINAL DIA (IN)	MATERIAL
BRACE RAIL	1.660	GALV TUBULAR STL
GATE FRAME	2.00	GALV TUBULAR STL
LINE POSTS	2.375	GALV TUBULAR STL
END & CORNER POST	2.875	GALV TUBULAR STL
CHAIN LINK FABRIC		9 GA. BLACK PVC COATING.
GATE OPENING (ft)	NOMINAL DIA (IN)	MATERIAL
15'	4	GALV TUBULAR STL
GATE POST		




## CHAIN LINK FENCE AND GATE

DRAWING NO. 1005

REVISED 07-18

**CleanWater Services**


1/2 " STAINLESS STEEL BALL VALVE  
(NORMALLY CLOSED)



NOTES:

1. INSTALL GAUGE AS SHOWN ON 1/2" DUCTILE IRON PIPE SADDLE WITH STAINLESS STEEL STRAP.
2. ALL PIPE AND FITTINGS SHALL BE SCHEDULE 80 STAINLESS STEEL WITH THREADED ENDS.
3. INSTALL PRESSURE GAUGE AND DIAPHRAGM SEAL PER MANUFACTURERS' REQUIREMENTS.
4. ACCEPTABLE ALTERNATIVE IS FLANGED ANNULAR SEAL, RED VALVE SERIES 45 OR APPROVED EQUAL WITH GLYCERIN FILL.
5. ANGLE  $1/2"$  TEE AT  $45^\circ$  SO PRESSURE GAUGE CAN BE VIEWED FROM ABOVE.

## FORCE MAIN PRESSURE GAUGE





YARD HYDRANT

DRAWING NO. 1009

REVISED 12-18

 CleanWater Services



**KEY NOTES:**

- ① 12" MIN TO LOWEST POINT OF RPBP OR STRAINER, WHICHEVER IS LOWER
- ② MOLDED FIBERGLASS ENCLOSURE, INSTALL ACCORDING TO MANUFACTURER INSTRUCTIONS. SECURE TO PAD WITH STAINLESS STEEL ANCHOR BOLTS.
- ③ 6" OF 3/4" MINUS CRUSHED ROCK, COMPACTED TO 95% MAXIMUM DRY DENSITY (STD PROCTOR)

**NOTE:**

1. WRAP EXPOSED WATER PIPE WITH HEAT TAPE AND PVC COATED PIPE INSULATION.
2. FOLLOW LOCAL PLUMBING CODE.

# REDUCED PRESSURE BACKFLOW PREVENTER


DRAWING NO. 1011

REVISED 012-18

 **CleanWater Services**

BYPASS MANHOLE  
FLAT TOP  
W/REINFORCEMENT  
OR  
RUBBER GASKET FLAT TOP  
W/REINFORCEMENT

LOCATE FRAME  
AND COVER OVER  
LEDGE OF AT  
LEAST 12" IN  
WIDTH




#6 BAR AROUND OUTSIDE OF OPENING  
#6 DIAGONALS BOTH SIDES OF OPENING  
#6 6" O.C. BOTH WAYS

NOTES:

1. ALL JOINTS AND RUBBER GASKETS SHALL CONFORM TO THE REQUIREMENTS OF ASTM C-433.
2. ALL MANHOLE SECTIONS SHALL CONFORM TO THE REQUIREMENTS OF ASTM C-478 AND APPLICABLE PROVISIONS OF STANDARD MANHOLE, SEE STD DRAWING NO. 010.
3. STEPS REQUIRED ON FLAT TOP MANHOLES DEEPER THAN 48" FROM FINISHED GRADE TO I.E. OUT.

RUBBER GASKET  
FLAT TOP  
(OPTIONAL)




BYPASS MANHOLE

SHEET NOTES:

1. PLACE NEW ANODE BAGS IN NATIVE SOIL AS PER SPECS. THERMITE WELD ANODE LEADS TO SERVICE SADDLE.
2. ALL STAINLESS STEEL PIPING SHALL BE SCHEDULE 40. ALL SMALL DIAMETER PVC SHALL BE SCHEDULE 80, SOLVENT WELDED JOINTS.
3. ALL ELECTRICALLY CONTINUOUS FITTINGS CONNECTED TO FORCE MAIN SHALL BE 316 STAINLESS STEEL, ALL OTHER FITTINGS, HARDWARE AND FASTENERS SHALL BE 304 STAINLESS STEEL UNLESS OTHERWISE NOTED.
4. SLOPE CONCRETE PAD MINIMUM 2% TOWARD 6" FLOOR DRAIN.
5. ORIENT DOOR AND LID OPENING LOCATION ON ENCLOSURE PER CWS DIRECTIONS AT EACH ARV LOCATION.
6. INSTALL DRAIN LINE IN SHARED TRENCH PER ENGINEER DETAIL. INSTALL STANDARD CLEANOUTS, PER DRAWING NO. 500, EVERY 300', OR WHERE SHOWN ON PLANS. DRAIN TO DISCHARGE TO NEAREST SANITARY SEWER MANHOLE AS SHOWN ON PLANS.
7. RAISE GRADE OF ARV BRANCH PIPING IF REQ'D TO AVOID CONFLICT W/ CROSSING UTILITIES. PROVIDE MINIMUM 5' COVER OVER PIPING W/IN ROADWAY.
8. ALL BURIED STAINLESS STEEL PIPING AND APPURTEANCES TO BE ELECTRICALLY CONTINUOUS AND COATED WITH WAX TAPE PER SPECIFICATIONS.
9. PROVIDE PERMANENT CAP ON 6" ARV DRAIN WHERE NOTED ON PLANS AND ALSO PROVIDE SIGN ON FLOOR DRAIN THAT IT IS NON-FUNCTIONAL.
10. ALL ITEMS NOTED ON TO BE FURNISHED BY OWNER SHALL BE INSTALLED BY CONTRACTOR
11. PROVIDE TRACER WIRE FOR 16" FM, 6" ARV DRAIN, AND 3" ARV PIPE, AS SHOWN ON DRAWING NO. 1016

KEY NOTES:

- 1 316 SST TAPPING SLEEVE W/ 3" OUTLET, SEE SPECS
- 2 3" SST NIPPLE, MIPT, OR 3" SST SPOOL, LENGTH AS REQUIRED
- 3 3" SST 90° BEND, FIPT
- 4 3" SST CLOSE NIPPLE
- 5 3" BURIED SST BALL VALVE
- 6 3" SST NIPPLE, MIPT X PE, LENGTH AS REQ'D
- 7 3" SST COMPRESSION COUPLING, SEE SPEC
- 8 3" SST 45° BEND, FIPT
- 9 3" SST BALL VALVE W/ LEVER HANDLE, MIPT
- 10 3" SST UNION
- 11 3" SST TEE, FIPT
- 12 2" ARV, VENT-O-MAT, OWNER FURNISHED, SEE NOTE 10, TYP
- 13 2" PVC NIPPLE, ADAPTER, OR SPOOL, AS REQ'D, OWNER FURNISHED
- 14 2" CAM-LOCK FITTING, FIPT, OWNER FURNISHED
- 15 2" POLYPROPYLENE CAM-LOCK FEMALE COUPLER, OWNER FURNISHED
- 16 2" FLEXIBLE HIGH TECH DURAVENT, UFD-AP URETHANE HOSE, OR APPROVED EQUAL, OWNER FURNISHED
- 17 6" X 2" PVC RDGR BUSHING, SCHED 80
- 18 6" PVC SPOOL, SCHED 80
- 19 6" PVC 90° BEND, SCHED 80
- 20 6" X 3" PVC TEE, ROLLED UP TO VENT, SCHED 80
- 21 6" PVC WYE, SCHED 80
- 22 6" FERNCO COUPLING, SCHED 80 PVC TO D3034 PVC OR PERMANENT 6" PVC CAP PER NOTE 9
- 23 6" D3034 SDR 35 PVC PIPE
- 24 6" D3034 SDR 35 PVC ELBOW FITTING, DEFL ANGLE AS REQ'D
- 25 6" D3034 SDR 35 PVC ELBOW FITTING, 90° ROLLED TO 2% MIN, OR AS REQ'D
- 26 3" SST BOLTED FLOOR FLG, FASTEN TO FLOOR W/ SST EPOXY ANCHORS
- 27 3"X2" SST HEX BUSHING, MNPTxFNPT
- 28 ARV ENCLOSURE, HOT BOX LB8FEM, COLOR PER SPEC, SEE NOTE 5
- 29 ANODE BAG, SEE NOTE 1
- 30 2" SST 90° BEND, FIPT, OWNER FURNISHED



AIR RELEASE VALVE ASSEMBLY  
PLAN VIEW

DRAWING NO. 1013

REVISED 08-18


CleanWater Services

**SHEET NOTES:**

1. PLACE NEW ANODE BAGS IN NATIVE SOIL AS PER SPECS. THERMITE WELD ANODE LEADS TO SERVICE SADDLE.
2. ALL STAINLESS STEEL PIPING SHALL BE SCHEDULE 40. ALL SMALL DIAMETER PVC SHALL BE SCHEDULE 80, SOLVENT WELDED JOINTS.
3. ALL ELECTRICALLY CONTINUOUS FITTINGS CONNECTED TO FORCE MAIN SHALL BE 316 STAINLESS STEEL. ALL OTHER FITTINGS, HARDWARE AND FASTENERS SHALL BE 304 STAINLESS STEEL UNLESS OTHERWISE NOTED.
4. SLOPE CONCRETE PAD MINIMUM 2% TOWARD 6" FLOOR DRAIN.
5. ORIENT DOOR AND LID OPENING LOCATION ON ENCLOSURE PER CWS DIRECTIONS AT EACH ARV LOCATION.
6. INSTALL DRAIN LINE IN SHARED TRENCH PER ENGINEER DETAIL. INSTALL STANDARD CLEANOUTS, PER DRAWING NO. 500, EVERY 300', OR WHERE SHOWN ON PLANS. DRAIN TO DISCHARGE TO NEAREST SANITARY SEWER MANHOLE AS SHOWN ON PLANS.
7. RAISE GRADE OF ARV BRANCH PIPING IF REQ'D TO AVOID CONFLICT W/ CROSSING UTILITIES. PROVIDE MINIMUM 5' COVER OVER PIPING W/IN ROADWAY.
8. ALL BURIED STAINLESS STEEL PIPING AND APPURTENANCES TO BE ELECTRICALLY CONTINUOUS AND COATED WITH WAX TAPE PER SPECIFICATIONS.
9. PROVIDE PERMANENT CAP ON 6" ARV DRAIN WHERE NOTED ON PLANS AND ALSO PROVIDE SIGN ON FLOOR DRAIN THAT IT IS NON-FUNCTIONAL.
10. ALL ITEMS NOTED ON TO BE FURNISHED BY OWNER SHALL BE INSTALLED BY CONTRACTOR
11. PROVIDE TRACER WIRE FOR 16" FM, 6" ARV DRAIN, AND 3" ARV PIPE, AS SHOWN ON DRAWING NO. 1016

### KEY NOTES:


<p>① 316 SST TAPPING SLEEVE W/ 3" OUTLET, SEE SPECS</p> <p>② 3" SST NIPPLE, MIPT, OR 3" SST SPOOL, LENGTH AS REQUIRED</p> <p>③ 3" SST 90° BEND, FIPT</p> <p>④ 3" SST CLOSE NIPPLE</p> <p>⑤ 3" BURIED SST BALL VALVE</p> <p>⑥ 3" SST NIPPLE, MIPT X PE, LENGTH AS REQ'D</p> <p>⑦ 3" SST COMPRESSION COUPLING, SEE SPEC</p> <p>⑧ 3" SST 45° BEND, FIPT</p> <p>⑨ 3" SST BALL VALVE W/ LEVER HANDLE, MIPT</p> <p>⑩ 3" SST UNION</p> <p>⑪ 3" SST TEE, FIPT</p> <p>⑫ 2" ARV, VENT-O-MAT, OWNER FURNISHED, SEE NOTE 10, TYP</p> <p>⑬ 2" PVC NIPPLE, ADAPTER, OR SPOOL, AS REQ'D, OWNER FURNISHED</p> <p>⑭ 2" CAM-LOCK FITTING, FIPT, OWNER FURNISHED</p> <p>⑮ 2" POLYPROPYLENE CAM-LOCK FEMALE COUPLER, OWNER FURNISHED</p> <p>⑯ 2" FLEXIBLE HIGH TECH DURAVENT, UFD-AP URETHANE HOSE, OR APPROVED EQUAL, OWNER FURNISHED</p>	<p>⑰ 6" X 2" PVC RDCR BUSHING, SCHED 80</p> <p>⑱ 6" PVC SPOOL, SCHED 80</p> <p>⑲ 6" PVC 90° BEND, SCHED 80</p> <p>⑳ 6" X 3" PVC TEE, ROLLED UP TO VENT, SCHED 80</p> <p>㉑ 6" PVC WYE, SCHED 80</p> <p>㉒ 6" FERNCO COUPLING, SCHED 80 PVC TO D3034 PVC OR PERMANENT 6" PVC CAP PER NOTE 9</p> <p>㉓ 6" D3034 SDR 35 PVC PIPE</p> <p>㉔ 6" D3034 SDR 35 PVC ELBOW FITTING, DEFL ANGLE AS REQ'D</p> <p>㉕ 6" D3034 SDR 35 PVC ELBOW FITTING, 90° ROLLED TO 2% MIN, OR AS REQ'D</p> <p>㉖ 3" SST BOLTED FLOOR FLG, FASTEN TO FLOOR W/ SST EPOXY ANCHORS</p> <p>㉗ 3"x2" SST HEX BUSHING, MNPTxFNPT</p> <p>㉘ ARV ENCLOSURE, HOT BOX LB8FEM, COLOR PER SPEC, SEE NOTE 5</p> <p>㉙ ANODE BAG, SEE NOTE 1</p> <p>㉚ 2" SST 90° BEND, FIPT, OWNER FURNISHED</p>
--	---



AIR RELEASE VALVE ASSEMBLY  
ELEVATION VIEW

DRAWING NO. 1014


REVISED 08-18



**MUSHROOM STYLE ARV VENT SECTION**

SCALE: NTS

A  
1013



NOTES:

1. NO ROCK GUARD REQUIRED IF OPERATOR NUT WITHIN 36" OF FINISH GRADE. WHERE DEPTH FROM ROCK GUARD TO OPERATOR NUT IS GREATER THAN 6'-0", INSTALL SECOND ROCK GUARD.

**VALVE BOX DETAIL**

SCALE: NTS


4  
1014

**MUSHROOM STYLE ARV VENT &  
VALVE BOX DETAILS**

DRAWING NO. 1015

REVISED 08-18


**CleanWater Services**



### TRACER BOX DETAIL

SCALE: NTS

1  
-



### PIPE WARNING SIGN DETAIL


SCALE: NTS

2  
-

### TRACER BOX & PIPE WARNING SIGN DETAILS

DRAWING NO. 1016

REVISED 08-18




NOTES:

1. MATERIAL: 316 STAINLESS STEEL
2. COORDINATE WITH OWNER AND ENGINEER ON LOCATION OF PUMP CHAIN HOLDER.
3. 1 PER PUMP, INSTALL AS HIGH AS POSSIBLE WITH OUT CONFLICTING WITH ACCESS HATCH.

**HEAVY DUTY CHAIN HOLDER DETAIL**  
SCALE: NTS

A  
1017



SYMBOL

BACKFILL REQUIREMENTS

**G**

FURNISH AND INSTALL CLASS 'D' BEDDING & PIPE ZONE & CLASS 'D' OR CLASS 'E' TRENCH BACKFILL AS SHOWN ON PLANS, TO PAVEMENT BASE. COMPACT MATERIAL IN LIFTS TO ACHIEVE 100% OF MAX DENSITY IN ACCORDANCE W/ AASHTO T-99. REPLACE REMOVED ASPHALT W/ 6" LEVEL 3 AC, SEE SPECS.

**N**

FURNISH & INSTALL CLASS 'D' BEDDING & PIPE ZONE BACKFILL COMPAKTED TO 95% OF MAX DENSITY PER AASHTO T-99. FURNISH & INSTALL CLASS 'B' NATIVE TRENCH BACKFILL TO FIN GR COMPAKTED TO 95% MAX DENSITY PER AASHTO T-99. REPLACE TOPSOIL & BACKFILL W/ CLASS 'B' NATIVE MATERIAL. FINISH TRENCH SURFACE TO MATCH ORIGINAL CONTOURS. REPLACE EXIST LANDSCAPING.

**NOTES:**


1. TAPE TRACER WIRE CONDUIT TO TOP OF PIPE EVERY 10-FEET. COLOR OF TONE WIRE INSULATION AND LOCATING TAPE SHALL BE AS FOLLOWS:

SAN FM:	GREEN
ELEC CONDUIT:	RED
FM ARV PIPE:	GREEN
SAN GRAVITY:	GREEN
PVC STORM:	GREEN

2. WORDING ON LOCATING TAPE SHALL BE AS FOLLOWS:

SAN FM:	CAUTION BURIED SEWER LINE BELOW
ELEC CONDUIT:	CAUTION BURIED ELECTRICAL LINE BELOW
FM ARV PIPE:	CAUTION BURIED SEWER LINE BELOW
SAN GRAVITY:	CAUTION BURIED SEWER LINE BELOW
PVC STORM:	CAUTION BURIED SEWER LINE BELOW


## SINGLE PIPE TRENCH DETAIL



**PAVEMENT/CURB EDGE & PLANTING BED SECTION DETAIL**

SCALE: NTS

A



**TREE PLANTING DETAIL**

SCALE: NTS



B

**LANDSCAPE DETAILS**

DRAWING NO. 1020

REVISED 08-18

**CleanWater Services**




## LANDSCAPE DETAILS

DRAWING NO. 1021

REVISED 08-18


CleanWater Services



**2 1/2" OR SMALLER GATE VALVE DETAIL**

SCALE: NTS

E



**3" OR LARGER GATE VALVE DETAIL**

SCALE: NTS


F

## LANDSCAPE DETAILS

DRAWING NO. 1022

REVISED 08-18


**CleanWater Services**



### EVERGREEN TREE PLANTING DETAIL

SCALE: NTS

G



### MANUAL DRAIN VALVE DETAIL

SCALE: NTS


H

## LANDSCAPE DETAILS

DRAWING NO. 1023

REVISED 08-18


 CleanWater Services



**REMOTE CONTROL VALVE DETAIL**

SCALE: NTS

I



**WINTERIZATION ASSEMBLY @ ALL MAIN VALVES DETAIL**

SCALE: NTS


J

**LANDSCAPE DETAILS**


DRAWING NO. 1024

REVISED 08-18

**CleanWater Services**



TYPICAL RISER DETAIL K  
SCALE: NTS



IRRIGATION AND CONTROL SLEEVE DETAIL L  
SCALE: NTS

## LANDSCAPE DETAILS

DRAWING NO. 1025

REVISED 08-18

 **CleanWater Services**

# SAMPLE DRAWING

FULL SIZE DRAWING WILL BE PROVIDED IN AUTOCAD FORMAT BY  
TREATMENT PLANT SERVICES AND SHALL BE USED BY DESIGN ENGINEER  
IN PREPARING PUMP STATION CONSTRUCTION DRAWINGS.

## ELECTRICAL ABBREVIATIONS, & SYMBOLS

STANDARD DRAWING NO. 1070B


ONE-LINE DIAGRAM SYM.	CONTROL SCHEMATIC SYM.	CONTROL SCHEMATIC SYM. CONT.	ELECTRICAL PLAN SYM.	LIGHTING PLAN SYM.
 LIGHTNING ARRESTOR  CURRENT TRANSFORMER X = NO. OF PHASES  POTENTIAL/VOLTAGE TRANSFORMER X = NO. OF PHASES  DRAW OUT OR STAB-IN CONNECTION  LOW VOLTAGE CIRCUIT BREAKER TRIP AMPERAGE/POLES/FRAME SIZE 20/3/50  FUSED SWITCH, FUSE RATING/POLES/SWITCH RATING NF = NON FUSED 30/3/60  LOW VOLTAGE DRAW OUT CIRCUIT BREAKER  MEDIUM VOLTAGE DRAW OUT BREAKER  TRANSFORMER WITH PRIMARY VOLTAGE, SECONDARY VOLTAGE, AND KVA RATING SHOWN 480 3 120/240V 7.5 KVA  TRANSFER SWITCH ATS = AUTOMATIC MTS = MANUAL  MAGNETIC STARTER W/THERMAL OVERLOADS  GENERATOR. X=RATING  MOTOR  INSTRUMENT SWITCH <u>SUBSCRIPT:</u> AS = AMMETER SWITCH VS = VOLTMETER SWITCH  SWITCHBOARD INSTRUMENT TYPE AS INDICATED  METERING TYPE AS INDICATED  NON-MOTOR LOAD WITH KW OR AMPERES RATING  AUXILIARY OR CONTROL DEVICE (CONTROL STATION SHOWN)  VARIABLE FREQUENCY DRIVE  DISCONNECT OR SAFETY SWITCH, NON-FUSED UNLESS OTHERWISE INDICATED  CONTROL PANEL SUPPLIED W/OTHER EQUIPMENT  SEPARATELY MOUNTED COMBINATION MOTOR STARTER OR CONTROLLER. SEE ELECTRICAL ONE LINE DIAGRAM OR SCHEDULE FOR DESCRIPTION  FIELD WIRING EXTERNAL TO CONTROL PANEL  SELECTOR SWITCH  MOTOR CONTROLLER TERMINAL 	 ON - OFF SWITCH  FLOAT SWITCH, CLOSE ON RISING LEVEL  PRESSURE SWITCH, CLOSE ON FALLING LEVEL  PRESSURE SWITCH, CLOSE ON INCREASING PRESSURE  PRESSURE SWITCH, CLOSE ON DECREASING PRESSURE  LIMIT SWITCH, CLOSE WHEN POSITION REACHED  LIMIT SWITCH, OPEN WHEN POSITION REACHED  TEMPERATURE SWITCH, CLOSE ON RISING TEMPERATURE  TEMPERATURE SWITCH, OPEN ON RISING TEMPERATURE  TOGGLE SWITCH (OPEN & CLOSED)  CONTACTOR COIL, CONTROL RELAY COIL, MOTOR STARTER COIL, OR SOLENOID VALVE COIL  CONTACTS, CONTACTOR, CONTROL RELAY OR MOTOR STARTER, CONTACTS, NORMALLY OPEN & NORMALLY CLOSED  THERMAL OVERLOAD RELAY AUXILIARY CONTACT  THERMAL OVERLOAD ELEMENT  PUSH TO TEST INDICATING LIGHT X INDICATES LENS COLOR  <p>LENS COLORS: R - RED      Y - YELLOW G - GREEN    W - WHITE B - BLUE     A - AMBER</p>  SINGLE CIRCUIT PUSHBUTTONS, NORMALLY OPEN & NORMALLY CLOSED  SELECTOR SWITCH (3-WAY SHOWN)  PROGRAMMABLE CONTROLLER INPUT ("AUTO" STATUS INDICATED)  PROGRAMMABLE CONTROLLER OUTPUT ("RUN" COMMAND INDICATED)	 TIME DELAY RELAY, TRX, TIMING RANGE AS NOTED TDAE = TIME DELAY PICK UP AFTER ENERGIZATION TDAD = TIME DELAY DROP OUT AFTER DE-ENERGIZATION  TIME DELAY RELAY CONTACT, NORMALLY OPEN, CLOSE AFTER TIME DELAY ON ENERGIZATION  TIME DELAY RELAY CONTACT, NORMALLY CLOSED, OPEN AFTER TIME DELAY ON ENERGIZATION  TIME DELAY RELAY CONTACT, NORMALLY OPEN, CLOSE ON ENERGIZATION, OPEN AFTER TIME DELAY ON DE-ENERGIZATION  HORN  FLOW SWITCH, CLOSE ON INCREASING FLOW  FLOW SWITCH, OPEN ON INCREASING FLOW  TOGGLE SWITCH (OPEN & CLOSED)  CONTACTOR COIL, CONTROL RELAY COIL, MOTOR STARTER COIL, OR SOLENOID VALVE COIL  CONTROL POWER TRANSFORMER, PRIMARY AND SECONDARY VOLTAGES AS NOTED, SIZE AS REQUIRED UNLESS NOTED  BROAD BAND FILTER FOR HARMONIC MITIGATION  POWER REACTOR X = NO. OF PHASES  METAL OXIDE VARISTOR  FUSE, FUSEBLOCK AND BLOWN FUSE INDICATOR  SINGLE CIRCUIT PUSHBUTTONS, NORMALLY OPEN & NORMALLY CLOSED  SELECTOR SWITCH (3-WAY SHOWN)  PROGRAMMABLE CONTROLLER INPUT ("AUTO" STATUS INDICATED)  PROGRAMMABLE CONTROLLER OUTPUT ("RUN" COMMAND INDICATED)	 GROUND  ELECTRICAL CONNECTION  CONDUIT SEAL  CONDUIT TURNED DOWN  CONDUIT TURNED UP  HOME RUN EXPOSED  HOME RUN CONCEALED  EXPOSED WIRING RUN, 3/4", 2 #12 W/1/2" G, UNLESS OTHERWISE NOTED  UNDERGROUND ELECTRICAL DUCT BANK CONCRETE-ENCASED UNLESS OTHERWISE NOTED  GROUND GRID OR CABLE  GROUND ROD  EXISTING UNDERGROUND ELECTRICAL DUCT BANK  UNDERGROUND TELEPHONE CONDUIT (CONCRETE-ENCASED UNLESS OTHERWISE NOTED)  OVERHEAD ELECTRICAL  ANTENNA  TRANSFORMER  POWER OR LIGHTING PANEL BOARD  CONTROL PANEL SUPPLIED WITH OTHER EQUIPMENT  DISCONNECT OR SAFETY SWITCH, NON-FUSED UNLESS OTHERWISE INDICATED  JUNCTION BOX P = PULLBOX TB = TERMINAL BOX  THERMOSTAT  CONDUIT TAG OR CIRCUIT NUMBER  AUXILIARY OR CONTROL DEVICE (CONTROL STATION SHOWN)  SOLENOID VALVE  INSTRUMENTATION  FS - FLOW SWITCH  H - HEATER  IL - INDICATION LIGHT  L.E.S - LEVEL SWITCH  PB - PUSHBUTTON STATION  PE - PNEUMATIC ELECTRIC STATION  PS - PRESSURE SWITCH  SC - SPEED CONTROL DEVICE  SI - SPEED INDICATOR  SS - SPEED SWITCH  SL - SEAL LEAK  HS.SW - SELECTOR SWITCH  TE - TEMPERATURE ELEMENT  TG - TACHOMETER GENERATOR  TS - TEMPERATURE SWITCH  XS,ZS - LIMIT SWITCH  XT - POSITION TRANSMITTER	 LUMINAIRE (HID OR INC)  EXIT SIGN, SHADeD AREAS INDICATE FACE(S)  FLUORESCENT LIGHT FIXTURE  SELF CONTAINED EMERGENCY LIGHT  EMERGENCY LIGHT, REMOTE MOUNTED HEAD  POLE MOUNTED LUMINAIRE  SWITCH  EMERGENCY LIGHT, 2 ATTACHED HEADS SHOWN <p><b>LUMINAIRE SUBSCRIPTS:</b></p> <p>X = FIXTURE TYPE, SEE FIXTURE SCHEDULE Y = CIRCUIT NUMBER FROM PANELBOARD Z = CONTROLLING SWITCH</p> <p><b>SWITCH SUBSCRIPTS:</b></p> <p>NONE = SINGLE-POLE SWITCH 3 = THREE-WAY SWITCH 4 = FOUR-WAY SWITCH M = MANUAL MOTOR STARTER WITH THERMAL ELEMENT FOR SMALL HORSEPOWER MOTOR PE = PHOTOELECTRIC WP = WEATHERPROOF SWITCH XP = EXPLOSIONPROOF SWITCH</p>
<p><b>RECEPTACLE SYM.</b></p>  DUPLEX TELEPHONE JACK (UNLESS OTHERWISE SHOWN ON DRAWINGS)  TELEPHONE JACK (UNLESS OTHERWISE SHOWN ON DRAWINGS)  125V, 20A DUPLEX RECEPTACLE, SPECIAL PURPOSE RECEPTACLE (AS DEFINED ON DRAWINGS)  PLUG-IN RECEPTACLE STRIP  HEAVY DUTY RECEPTACLE  HEAVY DUTY DUPLEX <p><b>RECEPTACLE SUBSCRIPTS:</b></p> <p>GFCI = GROUND FAULT CIRCUIT INTERRUPTER RECEPTACLE WP = WEATHERPROOF RECEPTACLE XP = EXPLOSIONPROOF RECEPTACLE</p>				
<p><b>GENERAL NOTES</b></p> <ol style="list-style-type: none"> <li>1. THIS IS A STANDARD ELECTRICAL SYMBOLS SHEET. ILLUSTRATION OF SYMBOL DOES NOT IMPLY ALL SYMBOLS HAVE BEEN USED ON THIS PROJECT.</li> <li>2. EMPTY CONDUITS SHALL BE PROVIDED WITH PULL ROPE AND BE CAPPED OR PLUGGED TO PREVENT WATER ENTRY.</li> <li>3. LIGHTING &amp; RECEPTACLE CIRCUIT CONDUITS &amp; CONDUCTORS ARE NOT SHOWN ON DRAWINGS. CONTRACTOR TO PROVIDE AND INSTALL LIGHTING &amp; RECEPTACLE CONDUITS AND CONDUCTORS REQUIRED TO OPERATE CIRCUITS.</li> </ol>				
DRN: ANV      ORIG DATE: 01/22/02	DSN: JTO      DWG #: E00	THIS BAR IS ONE INCH WHEN DRAWING IS FULL SCALE.	PROJ NAME: PUMP STATION STANDARD DRAWINGS	SHEET TITLE: ELECTRICAL ABBREVIATIONS & SYMBOLS
8/26/19 at 1:28pm By: CleanWater Services	File: \TFS\Aardvarks\Pump Stations\Standard Drawings\Electrical\2018-PS-STD\CAD\			

# SAMPLE DRAWING

FULL SIZE DRAWING WILL BE PROVIDED IN AUTOCAD FORMAT BY  
TREATMENT PLANT SERVICES AND SHALL BE USED BY DESIGN ENGINEER  
IN PREPARING PUMP STATION CONSTRUCTION DRAWINGS.

STANDARD DRAWING NO. 1071


## ELECTRICAL ONE LINE DIAGRAM



## SAMPLE DRAWING

FULL SIZE DRAWING WILL BE PROVIDED IN AUTOCAD FORMAT BY  
TREATMENT PLANT SERVICES AND SHALL BE USED BY DESIGN ENGINEER  
IN PREPARING PUMP STATION CONSTRUCTION DRAWINGS.

STANDARD DRAWING NO. 1072



Plotted: 8/26/19 at 1:31pm By: egglesony  
File: 1073.DWG  
Title: STANDARDS ELECTRICAL

DRN: ANV  
DSN:  
CHK: SW /  
APPD: JTC

THIS BAR IS ONE INCH  
WHEN DRAWING IS FULL  
SCALE.

PROJ NAME: PUMP STATIC  
STANDARD DRAWINGS

SHEET TITLE: ELECTRICAL  
INTERIOR ENCLOSURE - 01

T: 25 OF: 36	DWG #:
7/25/18	
NA	
XXXX	


LAST UPDATE  
07-25-2018

# SAMPLE DRAWING

FULL SIZE DRAWING WILL BE PROVIDED IN AUTOCAD FORMAT BY  
TREATMENT PLANT SERVICES AND SHALL BE USED BY DESIGN ENGINEER  
IN PREPARING PUMP STATION CONSTRUCTION DRAWINGS.

STANDARD DRAWING NO. 1073

## ELECTRICAL INTERIOR ENCLOSURE - 02



### KEYED NOTES & NAMEPLATE DESIGNATIONS:

ITEM NO.	DEVICE	NAMEPLATE
1	WEATHER PROOF ENCLOSURE	PUMP STATION XXXX
2	LOAD CENTER	LOAD CENTER
3	PANEL HEATER WITH INTEGRAL THERMOSTAT	CIRCUIT LP-7
4	NOT USED	
5	NOT USED	
6	DRY TYPE XMFR PRIM BREAKER	DRY TYPE XMFR PRIM BREAKER
7	DRY TYPE XMFR	
8	O & M RACK	O & M RACK
9	DUPLEX RECEPTACLE	CIRCUIT LP-9
10	2'x4' FLOURESCENT LIGHTS	
11	NOT USED	
12	AUTOMATIC TRANSFER SWITCH	AUTOMATIC TRANSFER SWITCH
13	NOT USED	
14	PANEL LIGHT ON/OFF (ACTIVATED BY DOOR OPENING)	
15	GROUND RODS & GROUND WIRE, #1	
16	NOT USED	
17	NOT USED	
18	PANEL EXHAUST FAN WITH FILTER AND LOUVER	CIRCUIT LP-7
19	PANEL EXHAUST THERMOSTAT	
20	MINIMUM 1/2" ANCHOR BOLT (STAINLESS STEEL)	
21	KWH METER BASE PER PGE STANDARDS	
22	MAIN BREAKER SS NEMA 4X	

### GENERAL NOTES:

- NOT USED
- INTERIOR RACEWAY ROUTING BETWEEN PANELS WITHIN ENCLOSURES SHALL BE WELL COORDINATED AND SHALL BE EMT TYPE.
- PROVIDE DESIGNATED PUMPSATION NAMEPLATE ON OUTSIDE FRONT ENCLOSURE i.e. XXXX PUMPSATION.
- PAD DETAILS AND CONNECTION TO PAD SHOULD BE DESIGNED TO RESIST SEISMIC AND WIND LOADS. THE DETAILS SHOWN SHOULD BE CONSIDERED MINIMUMS. SEE DETAIL DWG E11.
- RUNNING THREAD CONDUIT SHALL NOT BE USED.
- PVC COATED CONDUITS FROM FIELD EQUIPMENT SHALL BE INTERCEPTED WITH THE 6" METAL RACEWAY. COORDINATE THE ACTUAL RACEWAY LOCATION PRIOR TO HOME RUN CONDUITS INSTALLATION. SEE CONDUIT SCHEDULE.
- TRANSITION FROM UNDERGROUND OR CONCRETE EMBEDDED TO EXPOSED: PVC-COATED STEEL CONDUIT TO 12" BELOW GRADE. TYP.
- EXPOSED WIRE IS NOT ACCEPTABLE.
- KWH METER INSTALLED PER PGE MAX HEIGHT. MAIN BREAKER INSTALLED IMMEDIATELY BELOW METER.

DRN: ANV	ORIG DATE: 06/10/03
DSN:	DWG #: PS E03
CHK: SW / DP	CAD FILE #: 1073PS00E03
APPD: JTO	SCALE: NA

THIS BAR IS ONE INCH WHEN DRAWING IS FULL SCALE.	
3	02/17
2	4/07
1	2/07
REV #	DATE DRN APPD DESCRIPTION



2550 SW Hillsboro Hwy. Hillsboro, Oregon 97123-9379

PROJ NAME:  
PUMP STATION  
STANDARD  
DRAWINGS

SHEET TITLE:  
ELECTRICAL  
INTERIOR ENCLOSURE - 02

26 OF: 36	DWG #:
PLOT DATE: 7/25/18	
PLC #: NA	
OWS PROJ #: XXXX	


LAST UPDATE  
07-25-2018  
PS E03  
ENGR STAMP:

# SAMPLE DRAWING

FULL SIZE DRAWING WILL BE PROVIDED IN AUTOCAD FORMAT BY  
TREATMENT PLANT SERVICES AND SHALL BE USED BY DESIGN ENGINEER  
IN PREPARING PUMP STATION CONSTRUCTION DRAWINGS.


STANDARD DRAWING NO. 1074

## ELECTRICAL CONTROL PANEL DETAIL



FRONT  
APPROXIMATE  
ENCLOSURE SIZE  
36"X24"X8"

(NOTE 3) (NOTE 4)



INTERIOR  
33"X23  
BACKPANEL  
(SEE NOTES 1& 2)

SEE DWG E08

**A** PUMP SEQUENCE CONTROL PANEL (PSPC) - FRONT AND INTERIOR DETAILS

SEE SHEET E02

### KEYED NOTES & NAMEPLATE DESIGNATIONS (PSCP):

ITEM NO.	DEVICE	NAMEPLATE
1	PUMP SEQUENCE CONTROL PANEL	PUMP CONTROL PANEL
2	SELECTOR SWITCH	CONTROL POWER ON/OFF
3	GREEN LIGHT	CONTROL POWER ON
4	RUN TIME METER	-
5	-	PUMP 1
6	-	PUMP 2
7	RED LIGHT	RUNNING
8	SELECTOR SWITCH	H-O-A
9	ALTERNATOR SELECTOR SWITCH	LEAD SELECTOR PUMP1-ALT-PUMP2
10	AMBER LIGHT	SEAL LEAK
11	RESET PUSHBUTTON	OVER TEMP RESET
12	AMBER LIGHT	MOTOR OVER TEMP
13	RELAYS, 2 POLE	
14	RELAYS, 4 POLE	
15	TIMER, OFF DELAY	
16	TIMERS, ON DELAY	
17	ALTERNATING RELAY	
18	SEAL LEAK DETECTOR	
19	INTRINSICALLY SAFE RELAYS	
20	FLOAT SWITCHES, NO	
21	TERMINALS, PUMP SEQUENCE CONTROL PANEL WIRING	
22	TERMINALS, SEAL LEAK & OVERTEMP WIRING	
23	TERMINALS, INTRINSICALLY SAFE WIRING	
24	PUSHBUTTON, 1 N.O., 1 N.C.	HIGH LEVEL ALARM TEST
25	SELECTOR SWITCH, 2 POS, 1 N.O., 1 N.C.	HIGH LEVEL BEACON ALARM ENABLE-DISABLE
26	AMBER LIGHT	PUMP FAIL (OVERLOAD)
27	PUMP DIGITAL AMP DISPLAY	120 VAC
28	WELL LEVEL DIGITAL DISPLAY	

### NOTES:


1. PROVIDE PSCP WITH 10% EXTRA SPACE AND DOOR STOP
2. PROVIDE NAMEPLATES PER SPECIFICATION.
3. PROVIDE WETWELL OPERATING ELEVATION TABLE SETPOINTS ON FRONT OF PSCP PANEL
4. PROVIDE LABEL FOR EACH PILOT DEVICE ON THE BACK OF THE PANEL DOOR.

# SAMPLE DRAWING

FULL SIZE DRAWING WILL BE PROVIDED IN AUTOCAD FORMAT BY  
TREATMENT PLANT SERVICES AND SHALL BE USED BY DESIGN ENGINEER  
IN PREPARING PUMP STATION CONSTRUCTION DRAWINGS.

STANDARD DRAWING NO. 1075

## ELECTRICAL SEQUENCE CONTROL DIAGRAM



1 PUMP SEQUENCE CONTROL PANEL (PSCP) - CONTROL DIAGRAM  
E09

8/26/19 at 1:35pm By: egestorov  
Plotter: W:\PSCAD\Drawings\Pump Stations\STANDARDS\ELECTRICAL\2018 PS-STD\CAD\1075 DWG E05.dwg TAB: E05

DRN: ANV	ORIG DATE: 06/10/03
DSN:	DWG #: PS E05
CHK: SW / DP	CAD FILE #: 1075PS00E05
APPD: JTO	SCALE: NA

THIS BAR IS ONE INCH  
WHEN DRAWING IS FULL  
SCALE.

2	01/17	CG	JT	STANDARD DRAWINGS UPDATE
1	2/07	CAD	DP	MINOR REVISIONS
REV #	DATE	DRN	APPD	DESCRIPTION



2550 SW Hillsboro Hwy. Hillsboro, Oregon 97123-9379

PROJ NAME:  
PUMP STATION  
STANDARD  
DRAWINGS

SHEET TITLE:  
ELECTRICAL  
SEQUENCE CONTROL  
DIAGRAM


SHEET: 28 OF: 36  
PLOT DATE: 7/25/18  
DWG #: PS E05  
PLC #: NA  
CWS PROJ #: XXXX  
ENGR STAMP:

LAST UPDATE  
07-25-2018

## SAMPLE DRAWING

FULL SIZE DRAWING WILL BE PROVIDED IN AUTOCAD FORMAT BY  
TREATMENT PLANT SERVICES AND SHALL BE USED BY DESIGN ENGINEER  
IN PREPARING PUMP STATION CONSTRUCTION DRAWINGS.

STANDARD DRAWING NO. 1076



## GENERAL NOTES

- A. DESIGN IS BASED ON FLYGT PUMP CONTROL EQUIPMENT. CONTRACTOR TO PROVIDE ALTERNATE CONTROL EQUIPMENT IF OTHER PUMP MANUFACTURER IS SELECTED.
- B. CPT SHALL BE 480V OR 230V PER UTILITY PROVIDED POWER

## KEY NOTES

KEY NOTES		
ITEM	DESCRIPTIONS	COMMENTS
①	FUSES	FUSES TO BE SIZED PER MANUFACTURER'S RECOMMENDATIONS.
②	PUMP PROTECTION RELAY	FLYGT MINICAS 120 SENSOR. (PANEL MOUNTED). THERMAL CONTACT CLOSED IN "NORMAL" STATE, OPENING ON FAULT. MOISTURE CONTACT OPEN IN "NORMAL" STATE, CLOSING ON FAULT.
③	REMOTE DEVICE AND WIRING	DEVICES IN OUTLINED AREA ARE LOCATED IN THE PSCP. DASHED WIRING SHOWN IS REPRESENTATIVE OF NECESSARY WIRING BETWEEN RVSS CABINET AND PSCP CABINET.
④	RESISTOR	CONTRACTOR WILL PROVIDE AND INSTALL 1k OHM RESISTER PER RTU MFR REQUIREMENTS. SEE SHEET A-E-11.
⑤	BYPASS CONTACTOR	PROVIDE AND INSTALL NEMA SIZE 4, MINIMUM, BYPASS CONTACTOR.

## 1 CONTROL DIAGRAM MOTOR STARTER SUBMERSIBLE PUMP #1

1 E 06 SUBME NOT TO SCALE

DRN: ANV	ORIG DATE: 06/10/03
DSN:	DWG #: PS E06
CHK: SW / DP	CAD FILE #: 1076PS00E06A
APPD: JTO	SCALE: NA

THIS BAR IS ONE INCH  
WHEN DRAWING IS FULL  
SCALE.



2550 SW Hillsboro Hwy. Hillsboro, Oregon 97123-937

PROJ NAME: **PUMP STATION  
STANDARD  
DRAWINGS**

SHEET TITLE: ELECTRICAL  
STARTER SCHEMATICSS


SHEET: 29 OF: 36	DWG #:
PLOT DATE: 7/25/18	PS E06A
PLC #: NA	
CWS PROJ #: XXXX	

LAST UPDATE  
07-28-2018

## SAMPLE DRAWING

FULL SIZE DRAWING WILL BE PROVIDED IN AUTOCAD FORMAT BY TREATMENT PLANT SERVICES AND SHALL BE USED BY DESIGN ENGINEER IN PREPARING PUMP STATION CONSTRUCTION DRAWINGS.

STANDARD DRAWING NO. 1076




# SAMPLE DRAWING

FULL SIZE DRAWING WILL BE PROVIDED IN AUTOCAD FORMAT BY  
TREATMENT PLANT SERVICES AND SHALL BE USED BY DESIGN ENGINEER  
IN PREPARING PUMP STATION CONSTRUCTION DRAWINGS.

STANDARD DRAWING NO. 1077

ENCLOSURE AND RAIN HOOD  
DETAIL REFERENCE



## PROPRIETARY DATA

THE INFORMATION AND DESIGN(S) DISCLOSED HEREIN ARE THE PROPERTY OF HOFFMAN ENCLOSURES AND MAY NOT BE USED BY, OR DISCLOSED TO, ANY THIRD PARTY, EXCEPT AS GRANTED IN WRITING BY HOFFMAN ENCLOSURES INC. SIZE, LOCATION, AND ORIENTATION OF FEATURES SHOWN FOR INFORMATION PURPOSES ONLY.

PART NO.	N/A	A	ORIG ISSUE	11/01/02	TA
MATERIAL	SEE NOTES	REV	DESCRIPTION	DATE	BY
REFERENCE					
TO/FRNCE UNLESS NOTED		SCALE	NONE		
ONE PLACE (X) $\pm$ .1		DRWNS	TA		
TWO PLACE (XX) $\pm$ .01		THRE PLACE (XXX) $\pm$ .001	015		
ANGLES $\pm$ 2°		CHECKED	TA		
VELCRO $\pm$ .003		APPROVED	TA		
2D IDEAS DRAWING	DATE	11/01/02			
THREE WIRE	DO				
PROJECTION	NOT SCALE				
	DRAWING NO.				
	D	QUOTE 133563			


SHEET OF

# SAMPLE DRAWING

FULL SIZE DRAWING WILL BE PROVIDED IN AUTOCAD FORMAT BY  
TREATMENT PLANT SERVICES AND SHALL BE USED BY DESIGN ENGINEER  
IN PREPARING PUMP STATION CONSTRUCTION DRAWINGS.

STANDARD DRAWING NO. 1078

## ELECTRICAL INTRINSICALLY SAFE EXAMPLE



NOTES:


1. CABINET TO BE CONNECTED TO A GOOD GROUND
2. CAUTION - MAINTAIN SEPARATION BETWEEN INTRINSICALLY SAFE WIRING AND OTHER WIRING
3. WHEN MULTIPLE BARRIER MODULES ARE USED THE INTRINSICALLY SAFE CIRCUITS MUST EXIT THROUGH SEPARATE CONDUITS AND BE SEPARATED FROM EACH OTHER
4. INSTALL 750 OHM RESISTORS FOR INTRINSIC SAFETY PER SPECIFICATIONS.

# SAMPLE DRAWING


FULL SIZE DRAWING WILL BE PROVIDED IN AUTOCAD FORMAT BY  
TREATMENT PLANT SERVICES AND SHALL BE USED BY DESIGN ENGINEER  
IN PREPARING PUMP STATION CONSTRUCTION DRAWINGS.

STANDARD DRAWING NO. 1079

ELECTRICAL  
MECHANICAL DETAILS




4 CABLE TRENCH PHOTOS  
SCALE: NONE



NOTES:  
1. ALL HARDWARE GRADE 316 STAINLESS STEEL.  
2. CABLE HANGER SHALL BE PROVIDED FOR FLOATS, LEVEL SENSORS AND PUMPS. PROVIDE A TOTAL OF 6 HANGERS.  
3. INSTALL CABLE HANGER AS HIGH AS POSSIBLE WITHOUT CONFLICTING WITH ACCESS HATCH.

7 CABLE HANGER SECTION  
SCALE: NONE




NOTES:  
1. ALL BRACKETS AND MOUNTING HARDWARE TO BE 316 STAINLESS STEEL.  
2. PROVIDE WIRING METHODS SUITABLE FOR AREA CLASSIFICATION.  
3. TRANSITION CONCRETE FILL TO PROVIDE 6" CLEARANCE FROM END OF STILLING WELL.  
4. SEE ELECTRICAL DETAIL DWG PS10 NOTE 4 FOR CABLE TRENCH DETAIL.

6 LEVEL SENSOR MOUNTING DETAIL  
SCALE: NONE

STANDARD DRAWING NO. 1080


ELECTRICAL  
DISCONNECT AIR-GAP JUNCTION BOX DETAIL




1 FRONT VIEW DETAIL  
NTS




2a DISCONNECT AIR-GAP BOX  
NTS




2 PLAN VIEW DETAIL  
NTS




3 SIDE VIEW DETAIL  
NTS



4 CONDUIT TRANSITION DETAIL  
NTS



4a CONNECTION DETAIL  
NTS



4b MOUNTING DETAIL  
NTS

KEY NOTES		
ITEM	DESCRIPTIONS	COMMENTS
①	POWER DISTRIBUTION BLOCK	POWER DISTRIBUTION BLOCK WITH LUGS SIZED FOR MANUFACTURER'S PROVIDED POWER CABLING.
②	CONDUITS	CONDUITS TO VFD AND BACKUP CONTROL PANEL. ROUTE CONDUITS DOWN INTO GROUND WITHOUT FITTINGS.
③	NAMEPLATES	INSTALL EQUIPMENT NAMEPLATES ABOVE EACH POWER DISTRIBUTION BLOCK FOR EACH PUMP.
④	CABLE CHANNEL	CABLE CHANNEL TO WET WELL OLDCASTLE MOULDED PRODUCTS MODEL NO 128 PLASTIBETON CHANNEL SYSTEM COMPLETE WITH REMOVABLE COVER BUILT-IN SLOPE 1" HEAVY DUTY H-12 LOADING AND SMC DIVIDER TO PARTITION POWER CABLES FROM INSTRUMENTATION CABLES. SEE CIVIL DRAWINGS FOR PENETRATION TO WETWELL DETAIL.
⑤	HARDWARE	ALL HARDWARE, FRAMEWORK, ETC., SHALL BE STAINLESS STEEL.
⑥	AIR GAP POWER ENCLOSURE	30"H x 30"W x 10"D (MIN), 14GA, 304 STAINLESS ENCLOSURE WITH PADLOCK LOCKING RING FOR DOOR ATTACHED TO ENCLOSURE DOOR SHALL OPEN GREATER THAN 90 DEG. INSET SWING DOOR 2" FOR DRIP LIP.
⑦	AIR GAP CONTROL ENCLOSURE	20"H x 16"W x 10"D (MIN), 14GA, 304 STAINLESS ENCLOSURE WITH PADLOCK LOCKING RING FOR DOOR ATTACHED TO ENCLOSURE DOOR SHALL OPEN GREATER THAN 90 DEG. INSET SWING DOOR 2" FOR DRIP LIP.
⑧	HANDHOLE	HANDHOLE. 18'L x 12"W x 12"D. 2" THICK, MIN. WITH REINFORCING WIRE MESH, AND REMOVABLE COVER. NOTCH LID TO SEPARATE POWER AND CONTROL CABLES.
⑨	PUMP CABLES	VENDOR CABLES (POWER AND CONTROL) TO SUBMERSIBLE PUMPS LOCATED IN WET WELL.
⑩	FLOAT CABLE	VENDOR CABLES TO FLOAT SWITCH MOUNTED IN WETWELL.
⑪	LEVEL CABLES	VENDOR CABLES TO LEVEL TRANSDUCERS MOUNTED IN WETWELL.
⑫	I.S. SPACE	ENSURE SPACING OR PROVIDE BARRIER TO MAINTAIN DISTANCE FROM INTRINSICALLY SAFE WIRING TO OTHER WIRING PER NEC.
⑬	CORD GRIPS	PROVIDE J-HOOKS & KELUMS GRIPS TO SUPPORT ALL FLEXIBLE CORDS.

GENERAL NOTES:

A. RECEPTACLES AND MATCHING PLUGS FOR PUMP CONTROL CABLES SHALL MATCH THE ACTUAL PUMP PROVIDED CONTROL VOLTAGE.

DRN: ANV	ORIG DATE: 06/10/03
DSN:	DWG #: PS E10
CHK: SW / DP	CAD FILE #: 1080PS00E10
APPD: JTO	SCALE: NA

THIS BAR IS ONE INCH  
WHEN DRAWING IS FULL  
SCALE.

2	02/17	CG	JT	STANDARD DRAWINGS UPDATE
1	2/07	CAD	DP	MINOR REVISIONS
REV #	DATE	DRN	APPD	DESCRIPTION



2550 SW Hillsboro Hwy. Hillsboro, Oregon 97123-9379

PROJ NAME: PUMP STATION  
STANDARD  
DRAWINGS

SHEET TITLE: ELECTRICAL  
DISCONNECT AIR-GAP  
JUNCTION BOX DETAIL

SHEET: 34	OF: 36
PLOT DATE:	7/30/18
PLC #:	NA
CWS PROJ #:	XXXX

DWG #: PS E10

LAST UPDATE  
07-30-2018  
ENGR STAMP:

# SAMPLE DRAWING


FULL SIZE DRAWING WILL BE PROVIDED IN AUTOCAD FORMAT BY  
TREATMENT PLANT SERVICES AND SHALL BE USED BY DESIGN ENGINEER  
IN PREPARING PUMP STATION CONSTRUCTION DRAWINGS.

## ELECTRICAL DETAILS

STANDARD DRAWING NO. 1081

CONDUIT SCHEDULE							
TAG NO.	CONDUIT			CONDUCTORS			COMMENTS
	FROM	TO	SIZE	DESCRIPTION	FROM	TO	
C/P-GEN	ENCLOSURE 02	GENERATOR	1"	6# 10, 1# 10G	LOAD CENTER CKTS 10, 12, 14	APPROPRIATE DEVICE	SEE LOAD CENTER SCHEDULE ON SHEET 7 FOR CIRCUIT DESCRIPTIONS
				2# 12	ATS	GENERATOR CONTROL PANEL	FOR GENERATOR START CONTROL
				2# 12	WIREWAY	GENERATOR CONTROL PANEL	FOR GENERATOR RUNNING MONITORING- CONDUCTORS SHALL BE ROUTED TO AUTO DIALER VIA CONDUIT C-PSCP
C-FLOATS	ENCLOSURE 01	DISCONNECT AIR GAP J-BOX	1"	4# 14, 1# 14G	PSCP	FLOAT SWITCH CABLES RECEPTACLES	
C-PSCP	ENCLOSURE 01	ENCLOSURE 02	1"	2# 14, 1# 14G	MISSIONS	WIREWAY	CONDUCTORS SHALL BE ROUTED TO GENERATOR CONTROL PANEL VIA CONDUIT C/P-GEN
C-PUMPS	ENCLOSURE 01	DISCONNECT AIR GAP J-BOX	1"	4# 14, 1# 14G	PSCP	MOTOR SENSOR CABLES RECEPTACLES	
C-VAULT	ENCLOSURE 01	VALVE/METER VAULT	1"	4# 14, 1# 14G	PSCP	FLOOD SWITCHES IN VAULTS	SEE VAULT WIRING DIAGRAM, THIS SHEET
P-ATS	ENCLOSURE 01	ENCLOSURE 02	1-1/2"	3# 1, 1# 6G	POWER DISTRIBUTION BLOCK	ATS	
P-BFP HEAT	ENCLOSURE 02	BACKFLOW PREVENTOR	1"	2# 12, 1# 12G	LOAD CENTER CKT 13	HEAT TAPE	SEE NOTE 3
P-ENCL <sub>1/2</sub>	ENCLOSURE 01	ENCLOSURE 2	2"	PULLSTRING	N/A	N/A	SPARE
P-GEN	ENCLOSURE 02	GENERATOR	1"	3# 4, 1# 8G	ATS	GENERATOR BREAKER	
P-LC-1-7	ENCLOSURE 01	ENCLOSURE 2	1"	8# 10, 1# 10G	LOAD CENTER CKTS 1, 3, 5, 7	APPROPRIATE DEVICE	SEE LOAD CENTER SCHEDULE ON SHEET 7 FOR CIRCUIT DESCRIPTION
P-LC-2-8	ENCLOSURE 01	ENCLOSURE 02	1"	8# 10, 1# 10G	LOAD CENTER CKTS 2, 4, 6, 8	APPROPRIATE DEVICE	SEE LOAD CENTER SCHEDULE ON SHEET 7 FOR CIRCUIT DESCRIPTIONS
P-PGE	METER/ENCLOSURE 02	PGE SERVICE TRANSFORMER	4"	PULLSTRING	METER	PGE SERVICE TRANSFORMER	PROVIDE PER PGE REQUIREMENTS AND NOTE 1 ON SHEET 2
P-PUMP 1	ENCLOSURE 01	DISCONNECT AIR GAP-BOX	1"	3# 12, 1# 12G	PUMP 1 MOTOR STARTER	PUMP 1 DISCONNECT SWITCH	
P-PUMP 2	ENCLOSURE 01	DISCONNECT AIR GAP J-BOX	1"	3# 12, 1# 12G	PUMP 2 MOTOR STARTER	PUMP 2 DISCONNECT SWITCH	
P-TX BKR	ENCLOSURE 01	ENCLOSURE 02	1"	2# 10, 1# 10G	POWER DISTRIBUTION BLOCK	TRANSFORMER PRIMARY BREAKER	
S-FLOW	ENCLOSURE 01	VALVE/METER VAULT	1-1/2"	MSC & 1-TSP	FLOW TRANSMITTER	FLOW ELEMENT	NO SPLICES VIA JUNCTION BOX
S-LEVEL	ENCLOSURE 01	DISCONNECT AIR GAP J-BOX	1"	MSC	LEVEL TRANSMITTER	LEVEL ELEMENT	NO SPLICES


NOTE: THIS IS A SAMPLE CONDUIT SCHEDULE. PROVIDE PER SPECIFIC PROJECT.



CONCRETE PAD 2  
NTS

### KEYED NOTES:

- 1 PROVIDE SEAL-OFF FOR CLASS 1, DIV 2 AREA
- 2 PROVIDE JUNCTION BOX WITH 1/2" DRAIN HOLE IN BOTTOM FOR CABLES TO FLOW ELEMENT MOUNTED BELOW FLOW ELEMENT ELEVATION.




TYPICAL LIGHT POLE BASE 3  
NTS

# SAMPLE DRAWING

FULL SIZE DRAWING WILL BE PROVIDED IN AUTOCAD FORMAT BY  
TREATMENT PLANT SERVICES AND SHALL BE USED BY DESIGN ENGINEER  
IN PREPARING PUMP STATION CONSTRUCTION DRAWINGS.

STANDARD DRAWING NO. 1082

## ELECTRICAL MISSION RTU-INTERCONNECTION DIAGRAM



NOTE 1:  
THE CONTACT (H-O-A) SHALL  
OPEN WHEN H-O-A "A" SWITCH TO OFF POSITION

8/26/19 at 1:41 pm By: egestonv  
File: W:\TPS\Autocad\Standards\Electrical\2018 PS-STD\CAD\1081 DWG E12.dwg TAB: E12

DRN: CG	ORIG DATE: 02/14/17
DSN:	DWG #: PS E12
CHK: JT	CAD FILE #: 1082PS00E12
APPD: JT	SCALE: NA

THIS BAR IS ONE INCH WHEN DRAWING IS FULL SCALE.	
REV #	DATE DRN APPD DESCRIPTION

**CleanWater Services**  
Our commitment is clear.  
2550 SW Hillsboro Hwy. Hillsboro, Oregon 97123-9379

PROJ NAME: PUMP STATION  
STANDARD  
DRAWINGS  
SHEET TITLE: ELECTRICAL  
MISSION RTU  
INTERCONNECTION DIAGRAM

SHEET: 36 OF: 36  
PLOT DATE: 7/25/18  
PLC #: NA  
CWS PROJ #: XXXX  
DWG #: PS E12

LAST UPDATE  
07-25-2018  
ENGR STAMP: